FortiGate – iPhone 3G IPSec-VPN Setup Guide (v1.0)

Components	 All FortiGate Unit FortiOS v4.0 MR1 Patch1 (v4.1.1) iPhone 3G device
Last Modify	10-FEB-2010
Network IP Address	FortiGate: - WAN1 : 210.0.0.1/24 - DMZ : 10.0.0.99/24 - VPN : 172.16.1.0/255.255.255.0 (for iPhone user) WEB Server (Fortinet Knowledge Base) - IP : 10.0.0.100/24 (FortiGate DMZ I/F)
DMZ 10.0.100	Broadband Mobile Network Network VNN1 210.0.1 Visit Office Office Phone 3G Device Dec VPN Tunnel Dec VPN Tunnel Server Server
Procedure	 Setup FortiGate 1.1. Local ID and Password for iPhone(VPN) user 1.2. User Group for Local ID 1.3. Firewall address for DMZ access

1.Setup FortiGa	te
	3.3. WEB access over VPN (mobile network)
	3.2. Ping
	3.1. check to VPN connection status
	3.connection test for iPhone 3G device
	2.1.VPN
	·
	2 . Setup iPhone 3G device
	1.7. Firewall Policy
	1.6.DCHP address for VPN client (iPhone)
	1.5. VPN phase2
	1.4. VPN phase1

1.1. Edit Local ID and password for iPhone(VPN) user

Setup via WEB based manager:

- 1.1.1. Move to User > Local > Create New.
- 1.1.2. Enter User ID and Password.

	Edit User
User Name	test1
	Disable
Password	•••••
○ LDAP	[Please Select] 💉
○ RADIUS	[Please Select] 💌
○ TACACS+	[Please Select] 💌
1 1 2 Select OK	
1.1.3. Select OK.	
1.1.3. Select OK.	ip for Local ID
1.1.3. Select OK. 2. Edit User grou 1.2.1. Move to User	u p for Local ID > User Group > Create New.
1.1.3. Select OK. 2. Edit User grou 1.2.1. Move to User 1.2.2. Enter group na	u <mark>p for Local ID</mark> > User Group > Create New. ame (e.g. group1), and then select firewa
 1.1.3. Select OK. .2. Edit User grou 1.2.1. Move to User 1.2.2. Enter group na Select local ID from 	u p for Local ID > User Group > Create New. ame (e.g. group1), and then select firewa a available Users/Groups list.

	E	lit User Group
Name	group1	
Туре	Firewall 💌	
Available Use	ers/Groups	Members
test1 - Users on R - PKI Users -	ADIUS/LDAP/TACACS+ servers	- Users on RADIUS/LDAP/TACACS+ servers - - PKI Users -
test1 - Users on R - PKI Users - FortiGuard	ADIUS/LDAP/TACACS+ servers I Web Filtering Override	- Users on RADIUS/LDAP/TACACS+ servers - - PKI Users -

1.3. Edit Firewall address for DMZ access

- 1.3.1. Move to Firewall > Address > Create New.
- 1.3.2. Enter DMZ server info.
- 1.3.3. Enter address name, type, subnet/IP range, and interface.

Address Name	DMZ_WebServer	
Туре	Subnet / IP Range ⊻	
Subnet / IP Range	e 10.0.0.0/255.255.255.0	
Interface	dmz(Servers)	¥
	ОК	Cancel
.3.4. Select OK.		
3.5 Click Create	e new again	
.3.5. Click Create	e new again.	
.3.5. Click Create .3.6. Edit Firewall	e new again. address for iPhone user.	
.3.5. Click Create .3.6. Edit Firewall .3.7. Enter addres	e new again. address for iPhone user. ss name, type, subnet/IP ra	ange, and interface.
.3.5. Click Create .3.6. Edit Firewall .3.7. Enter addres	e new again. address for iPhone user. ss name, type, subnet/IP ra	ange, and interface.
.3.5. Click Create .3.6. Edit Firewall .3.7. Enter addres	e new again. address for iPhone user. ss name, type, subnet/IP ra Edit	ange, and interface. Address
3.5. Click Create 3.6. Edit Firewall 3.7. Enter addres Address Name	e new again. address for iPhone user. s name, type, subnet/IP ra Edit iPhoneVPNUsers	ange, and interface. Address
.3.5. Click Create .3.6. Edit Firewall .3.7. Enter address Address Name Type	e new again. address for iPhone user. as name, type, subnet/IP ra Edit iPhoneVPNUsers Subnet / IP Range 💌	ange, and interface. Address
3.5. Click Create 3.6. Edit Firewall 3.7. Enter addres Address Name Type Subnet / IP Range	e new again. address for iPhone user. is name, type, subnet/IP ra Edit iPhoneVPNUsers Subnet / IP Range V 172.16.1.0/255.255.255.0	ange, and interface. Address
3.5. Click Create 3.6. Edit Firewall 3.7. Enter address Address Name Type Subnet / IP Range Interface	e new again. address for iPhone user. is name, type, subnet/IP ra Edit iPhoneVPNUsers Subnet / IP Range 172.16.1.0/255.255.255.0 Any	ange, and interface.
3.5. Click Create 3.6. Edit Firewall 3.7. Enter address Address Name Type Subnet / IP Range Interface	e new again. address for iPhone user. as name, type, subnet/IP ra Edit iPhoneVPNUsers Subnet / IP Range 172.16.1.0/255.255.255.0 Any OK	Address

1.4. Edit VPN Phase1

Setup via WEB based manager:

1.4.1. Move to VPN > IPSec > auto Key > Create Phase1.

Enter following info.

Name	iPhone
Remote Gateway	Dialup users
Local Interface	WAN1
Mode	Main
Authentication Method	Pre-shared Key
Pre-shared Key	Key (same as iPhone3G VPN configuration)
Peer Options	Accept any peer ID

1.4.2. Select Advance option and then enter following info.

Enable IPsec Interface Mode	Enable
Local gateway IP	Main interface IP
1 Encryption	AES256
1 Authentication	MD5
2 Encryption	AES256
2 Authentication	SHA1
DH Group	2
Key life (sec)	28800
XAUTH	Enable as Server
Server Type	AUTO
	group1 (when you created it
	at 1.2 section)
NAT Traversal	Enable
Dead Peer Detection	Enable

1.4.3. Select OK.

1.5.Edit VPN Phase2

Setup via WEB based manager:

1.5.1. Move to VPN > IPSec > Auto Key > Create Phase2.

1.5.2. Enter following info.

|--|

Phase1

iPhone-P2 Select Phase1 name(iPhone)

1.5.3. Select Advanced option and then enter following info.

1 Encryption	AES256
1 Authentication	MD5
2 Encryption	AES256
2 Authentication	SHA1
Enable replay detection	Enable
PFS	Enable
DH Group	2
Key life(sec)	1800
Auto-key keep arrive	Enable
Quick mode selector	Source Address: 0.0.0.0/0.0.0.0 Destination Address: 0.0.0.0/0.0.0.0

1.5.3. Select OK.

1.6. Edit DHCP address for iPhone VPN client

1.6.1. Login to FortiGate via CLI. Then use following commands.

Command	comment
config vpn ipsec phase1-interface	Move to VPN phase1
edit iPhone	Edit VPN Phase1 configuration.
set mode-cfg enable	Enable mode-cfg
set ipv4-start-ip 172.16.1.1	DHCP start IP address
set ipv4-end-ip 172.16.1.254	DHCP end IP address
set ipv4-netmask 255.255.255.0	Subnet mask
set ipv4-split-include	For VPN user access to DMZ address
"DMZ_WebServer"	group.

1.7. Edit Firewall Policy

Setup via WEB based manager:

- 1.7.1. Move to Firewall Policy > Policy > Create new.
- 1.7.2. Enter following info.

Source Interface/Zone	iPhone
	(IPSec-VPN Interface)
Source Address	iPhoneVPNUsers
Destination Interface/Zone	DMZ
Destination Address	DMZ_WebServer
Schedule	Always
Service	ANY
Action	Accept

2.Setup iPhone 3G device

Cancel VPN TEST Save Create new profile. Description VPN TEST [VPN account info]]	
Description VPN TEST [VPN account info]	
Server 210.0.0.1	
Account Test1 Description VPN TEST (unique	name)
VPN Gateway addr	ess
Password •••••••• (FortiGate WAN1 I	P addres
Use Certificate OFF Account User ID	
Group Name Password Password	
Secret Off	
Pre-shared Key (sa	ame as
L OCROF	

VPN Stat	us
Server	210.0.0.1
Connect Time	21:29
Connected to	210.0.0.1
IP Address	172.16.1.1

3.1. Confirm to VPN access

When you finished VPN configuration on iPhone 3G device. Please dial-up 3G network and then connect VPN gateway (FortiGate). After that you can see connection status when VPN tunnel is up.

[Status]

Server VPN Gateway

			(FortiGate WAN1 IP address)
		Connect Time	Tunnel up time
		Connect to	VPN Gateway
	IP address	IP address release by DHCP. *refer to section 1.6.	
	<u> </u>		

<u>3.2.</u>	Ping

Star

Open Ping tool and then send ping packet to WEB server IP address (e.g. 10.0.0.100) behind of FortiGate DMZ network. You can confirm to receive response from server.

Note: Ping tool doesn't default apps on iPhone 3G device. You will need download it from somewhere (e.g. iTunes Store)



Ping

Either a DNS name or a raw IP address as 192.168.

back

IP address:

Output:

10.0.0.100

PING 10.0.0.100 (10.0.0.100) *Pinging host 10.0.0.100: icmp_seq=0 Resp. 10.0.0.100: seq=0 ttl=127 477 ms

*Pinging host 10.0.0.100: icmp_seq=1 Resp. 10.0.0.100: seq=1 ttl=127 449 ms *Pinging host 10.0.0.100: icmp_seq=2 Resp. 10.0.0.100: seq=2 ttl=127 489 ms *Pinging host 10.0.0.100: icmp_seq=3 Resp. 10.0.0.100: seq=3 ttl=127 469 ms

--- 10.0.0.100 ping statistics ---4 packets transmitted, 4 packets received, 0% packet loss

3.3.WEB access

Open WEB browser and then enter WEB server IP address (e.g. 10.0.0.100) behind of FortiGate DMZ network. You can confirm to see some contents of corporate internal resource.

Those IP addresses are for evaluation purpose. Please ask your ISP when you need public IP address.